

G5031020A

Led Power Supply CV AED20-24VIP44-3A-Q3 24V 20W

April 04th, 2025, 05:06



LETARON

DESCRIPTION

Slimline Led power supply for independent use with constant voltage output. IP44 protection. Primary wiring with 15cm 2x1mm² round hose cable for connection to the network and for the anti-fog. Three 15cm single-pole cables. in secondary + c-w-. On the back it has 3 sensors to be placed directly on the back of the mirror. Integrated Relay for demister. Ease installation and cost savings. Sensor 1. On/Off anti-fog function; Sensor 2. dimmer function; Sensor 3 CTT.

PRICE

Lot	P.V.P. excluding VAT
1	22,02€
5	18,36€
10	16,69€
100	15,60€

Continued on next page >>

G5031020A

Led Power Supply CV AED20-24VIP44-3A-Q3 24V 20W

TECHNICAL SPECIFICATIONS

SYMBOLS

CERTIFICADOS



SELV



(EMC)



Weight: 800 Grams

NOTES

Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.

OTHER FEATURES

Length (mm): 228,2

High (mm): 18

Voltage In (Vac): 220~240

Intensidad Out (A): 0.83

Power (W): 0~20

Critical Temperature (°C): 85

Ingress Protection: IP44

Power factor: 0.85

Width (mm): 126,2

Colour: White

Voltage Out (Vdc): 24

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+40

Life (Hours): 30000

Dimmable: SI

DOCUMENTS

[Data Sheet](#)

[Led Power Supply CV AED20-24VIP44-3A-Q3 24V 20W](#)

[Electromagnetic compatibility](#)