

G5031150L

Led Power Supply CV PW60-24 24V 150W

January 22nd, 2025, 08:04



DESCRIPTION

Led power supply for independent use with constant voltage output of 24Vdc. IP67. Primary and secondary wiring with 30cm. VDE rubber cable H05RN-F 2x1.0mm². On <0.5sec. No-load consumption <0.5W. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure. ECO design according to ERP directives. Efficiency 87%. Guarantee 3 years.

PRICE

Lot	P.V.P. excluding VAT
1	36,80€
5	33,45€
10	30,41€
50	28,42€



Continued on next page >>

G5031150L

Led Power Supply CV PW60-24 24V 150W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



(LVD)



Weight: 440 Grams

Packging: Box 20 Units

NOTES

ECO ERP design. Constant voltage output 24Vdc. Cabling.

OTHER FEATURES

Length (mm): 180

High (mm): 32

Voltage In (Vac): 220~240

Intensidad Out (A): 0~6.15

Power (W): 0~150

Critical Temperature (°C): 85

Ingress Protection: IP67

Power factor: 0.95

Width (mm): 52

Colour: White

Voltage Out (Vdc): 24

Frecuency (Hz): 50~60

Room Temperature (°C): -40~+50

Life (Hours): 50000

Dimmable: NO

DOCUMENTS

[Data Sheet](#)

[Led Power Supply CV PW60-24 24V 150W](#)

[CB](#)

[Electromagnetic Compatibility TUV](#)

[LVD \(DIRECTA BAJO VOLTAJE\)](#)

[Safety TUV CERTIFIED](#)