

G5031030C

LED Power Supply CV SLT30-24VFC-UN IP67 24V 30W

October 02nd, 2024, 03:22



DESCRIPTION

Extra-flat IP67 LED power supply for independent use with 24Vdc constant voltage output. Metal casing. Wiring with 15cm tripolar hose at the inlet and bipolar at the outlet. On <0.5sec. Consumption without load <0.5W. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure. ECO design according to ERP directives. 84.5% efficiency. 5-year warranty. Complies with EN60335 and can be used inside a refrigerator or freezer

PRICE

Lot	P.V.P. excluding VAT
1	37,36€
5	33,96€
10	30,89€
50	28,85€

Continued on next page >>

G5031030C

LED Power Supply CV SLT30-24VFC-UN IP67 24V 30W

TECHNICAL SPECIFICATIONS

SYMBOLS

SELV



CERTIFICADOS



Weight: 224 Grams

Packging: Box 1 Unit

NOTES

ECO Desogn ERP. IP67. Extra flat. Constant voltage output 24Vdc. Efficiency 84.5%

OTHER FEATURES

Length (mm): 275

Width (mm): 30

High (mm): 16

Colour: Grey

Voltage In (Vac): 120~240

Voltage Out (Vdc): 24

Intensidad Out (A): 0~1.25

Frecuency (Hz): 50~60

Power (W): 0~30

Room Temperature (°C): -20~+50

Critical Temperature (°C): 75

Ingress Protection: IP67

Dimmable: NO

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply CV SLT30-24VFC-UN IP67 24V 30W](#)

 [CE](#)

 [MEEI \(Hungary\)](#)

 [Regulatory Compliance Mark for Australia](#)