

G5030075A

LED Power Supply CV SLT75-12VFC-UN IP67 12V 75W

November 21st, 2024, 14:04



DESCRIPTION

Extra-flat IP67 LED power supply for independent use with 12Vdc constant voltage output. Metal casing. Wiring with 15cm tripolar hose at the inlet and bipolar at the outlet. On <0.5sec. Consumption without load <0.5W. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure. ECO design according to ERP directives. Efficiency 90.7%. 5-year warranty. Complies with EN60335 and can be used inside a refrigerator or freezer

PRICE

Lot	P.V.P. excluding VAT
1	51,45€
5	46,77€
10	42,52€
50	39,74€

Continued on next page >>

G5030075A

LED Power Supply CV SLT75-12VFC-UN IP67 12V 75W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CERTIFICADOS

CB



Weight: 230 Grams

Packging: Box 1 Unit

NOTES

Meets SLR-2021. IP67. Extra-flat. 12Vdc constant voltage output. Efficiency 90.7%. 60W (120V) 75W (240V)

OTHER FEATURES

Length (mm): 333

Width (mm): 30

High (mm): 16,5

Colour: Grey

Voltage In (Vac): 120~240

Voltage Out (Vdc): 12

Intensidad Out (A): 0~6.25

Frecuency (Hz): 50~60

Power (W): 0~75

Room Temperature (°C): -20~+50

Critical Temperature (°C): 75

Ingress Protection: IP67

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [CB](#)

 [CE](#)

 [MEEI \(Hungary\)](#)

 [Regulatory Compliance Mark for Australia](#)