

G5031075B

LED Power Supply CV SLT75-24VFC-UN IP67 24V 75W

November 21st, 2024, 19:11



DESCRIPTION

Extra-flat IP67 LED power supply for independent use with 24Vdc constant voltage output. Metal casing. Wiring with 15cm tripolar hose at the inlet and bipolar at the outlet. On <0.5sec. Consumption without load <0.5W. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure. ECO design according to ERP directives. 91.2% efficiency. 5-year warranty. Complies with EN60335 and can be used inside a refrigerator or freezer

PRICE

Lot	P.V.P. excluding VAT
1	51,35€
5	46,68€
10	42,45€
50	39,68€



G5031075B

LED Power Supply CV SLT75-24VFC-UN IP67 24V 75W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



Weight: 230 Grams

Packging: Box 1 Unit

NOTES

Meets ECO Design ERP. IP67. Extra-flat. 24Vdc constant voltage output. 91.2% efficiency.

OTHER FEATURES

Length (mm): 333

High (mm): 16

Voltage In (Vac): 120~240

Intensidad Out (A): 0~3.125

Power (W): 0~75

Critical Temperature (°C): 75

Dimmable: NO

Width (mm): 30

Colour: Grey

Voltage Out (Vdc): 24

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+50

Ingress Protection: IP67

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply CV SLT75-24VFC-UN IP67 24V 75W](#)

 [CE](#)

 [MEEI \(Hungary\)](#)