

G503540H

Led Power Supply dimmable CC NTF 700mA 40W

December 04th, 2024, 19:43



DESCRIPTION

Led power supply for independent use dimmable 1-100% with leading or trailing edge dimmers . Class II. 700mA constant current output. Output voltage from 28 to 56Vdc. Power range 20-40W. Screw terminals for cables from 0.75 to 2.5mm2 section. 86% efficiency. Protection against open circuit, short circuit, overload and overtemperature. Automatic reset in case of failure. Very low ripple current throughout the regulation range.

PRICE

Lot	P.V.P. excluding VAT
1	17,99€
5	14,99€
10	13,62€
50	12,74€

Continued on next page >>

G503540H

Led Power Supply dimmable CC NTF 700mA 40W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



**UK
CA**



Weight: 190 Grams

NOTES

ECO Design ERP Compliant. Dimmable with leading or trailing edge dimmers . Constant current output 700mA.

OTHER FEATURES

Length (mm): 166

Width (mm): 52

High (mm): 24

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 28~56

Intensidad In (A): 0.3

Intensidad Out (A): 0.7

Frecuency (Hz): 50~60

Power (W): 20~40

Room Temperature (°C): -20~+50

Critical Temperature (°C): 80

Life (Hours): 30000

Ingress Protection: IP20

Dimmable: Corte inicio o fin de fase

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [Led Power Supply dimmable CC NTF 700mA 40W](#)

 [ROHS](#)

 [CB](#)

 [EMC TUV CERTIFIED](#)

 [Safety TUV CERTIFIED](#)