

G503530

LED Power Supply dimmable SLD30-500IL-Es 500mA 30W

March 10th, 2025, 00:05



DESCRIPTION

Led power supply for independent use adjustable 10-100% with regulators cut start or end of phase. Class II. Constant current output 500mA. Output voltage from 30 to 60 Vdc. Power range 15-30W. 86% efficiency. Protection against open circuit, short circuit, overload and overtemperature. Automatic reset in case of failure. Very low ripple current throughout the regulation range. Warranty 5 years.

PRICE

Lot	P.V.P. excluding VAT
1	19,93€
5	18,11€
10	16,46€
50	15,39€



Continued on next page >>

G503530

LED Power Supply dimmable SLD30-500IL-Es 500mA 30W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



RoHS
COMPLIANT

CE



Weight: 220 Grams

Packging: Box 1 Unit

NOTES

ECO Design ERP Compliant. Dimmable 10-100% with leading or trailing edge dimmers. Constant current output 500mA.

OTHER FEATURES

Length (mm): 165

Width (mm): 40

High (mm): 30

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 30~60

Intensidad Out (A): 0.5

Frecuency (Hz): 50~60

Power (W): 15~30

Room Temperature (°C): -20~+40

Critical Temperature (°C): 75

Ingress Protection: IP20

Dimmable: Corte inicio o fin de fase

Power factor: 0.9

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply dimmable SLD30-500IL-Es 500mA 30W](#)

 [MEEI \(Hungary\)](#)

 [Regulatory Compliance Mark for Australia](#)