

G503530A

LED Power Supply dimmable SLD30-600IL-Es 600mA 30W

December 04th, 2024, 19:07



DESCRIPTION

Led power supply for independent use adjustable 10-100% with regulators cut start or end of phase. Class II. 600mA constant current output. Output voltage from 25 to 50 Vdc. Power range 15-30W. 86% efficiency. Protection against open circuit, short circuit, overload and overtemperature. Automatic reset in case of failure. Very low ripple current throughout the regulation range. 5 year warranty

PRICE

Lot	P.V.P. excluding VAT
1	19,93€
5	18,11€
10	16,46€
50	15,39€



Continued on next page >>

G503530A

LED Power Supply dimmable SLD30-600IL-Es 600mA 30W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



RoHS
COMPLIANT



Weight: 220 Grams

Packging: Box 1 Unit

NOTES

ECO Design ERP Compliant. Dimmable 10-100% with leading or trailing edge dimmers. Constant current output 600mA.

OTHER FEATURES

Length (mm): 165

High (mm): 30

Voltage In (Vac): 220~240

Intensidad Out (A): 0.6

Power (W): 15~30

Critical Temperature (°C): 75

Dimmable: Corte inicio o fin de fase

Width (mm): 40

Colour: White

Voltage Out (Vdc): 25~50

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+40

Ingress Protection: IP20

Power factor: 0.9

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply dimmable SLD30-600IL-Es 600mA 30W](#)

 [MEEI \(Hungary\)](#)

 [Regulatory Compliance Mark for Australia](#)