

## G503530B

### LED Power Supply dimmable SLD30-700IL-Es 700mA 29,4W

March 10th, 2025, 00:08



## DESCRIPTION

Led power supply for independent use adjustable 10-100% with regulators cut start or end of phase. Class II. 700mA constant current output. Output voltage from 21 to 42 Vdc. Power range 14.7-29.4W. 86% efficiency. Protection against open circuit, short circuit, overload and overtemperature. Automatic reset in case of failure. Very low ripple current throughout the regulation range. Warranty 5 years.

## PRICE

Lot	P.V.P. excluding VAT
1	19,93€
5	18,11€
10	16,46€
50	15,39€



Continued on next page >>

G503530B

**LED Power Supply dimmable SLD30-700IL-Es 700mA 29,4W**

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



**SELV**



**RoHS**  
COMPLIANT

**CE**



Weight: 220 Grams

Packging: Box 1 Unit

### NOTES

---

ECO Design ERP Compliant. Dimmable 10-100% with leading or trailing edge dimmers. Constant current output 700mA.

### OTHER FEATURES

---

Length (mm): 165

Width (mm): 40

High (mm): 30

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 21~42

Intensidad Out (A): 0.7

Frecuency (Hz): 50~60

Power (W): 14.7~29.4

Room Temperature (°C): -20~+40

Critical Temperature (°C): 75

Ingress Protection: IP20

Dimmable: Corte inicio o fin de fase

Power factor: 0.9

### DOCUMENTS

---

 [Data Sheet](#)

 [LED Power Supply dimmable SLD30-700IL-Es 700mA 29,4W](#)

 [MEEI \(Hungary\)](#)

 [Regulatory Compliance Mark for Australia](#)