

G5037160

**Led Power Supply Multi-current LED SLT160-700IL-EU jusqu'à 700mA 160W**

December 04th, 2024, 08:58



**DESCRIPTION**

Led power supply to incorporate with constant current multi-current output by DIP switch Class I. Quick connection terminals; 350mA 42-80W; 400mA 48-91W; 450mA 54-103W; 500mA 60-1140W; 550mA 66-125W; 600mA 72 -137W; 650mA 78- -148W; 700mA 24-160W.

Protection against open circuit, short circuit, over load and over temperature. Rearmament

**PRICE**

Lot	P.V.P. excluding VAT
1	27,77€
5	25,25€
10	22,96€
50	21,45€



Continued on next page >>

G5037160

Led Power Supply Multi-current LED SLT160-700IL-EU jusqu'à 700mA 160W

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



### CERTIFICADOS

Weight: 237 Grams

Packging: Box 1 Unit

## NOTES

---

SLR-2021 Compliant. Selectable constant output current from 350mA to 700mA by DIP switch.

## OTHER FEATURES

---

Length (mm): 280

Width (mm): 30

High (mm): 22

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 120~228

Intensidad Out (A): 0.35~0.7

Frecuency (Hz): 50~60

Power (W): 42~160

Room Temperature (°C): -20~+50

Critical Temperature (°C): 90

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.95

## DOCUMENTS

---

 [Data Sheet](#)

 [Led Power Supply Multi-current LED SLT160-700IL-EU jusqu'à 700mA 160W](#)

 [MEEI \(Hungary\)](#)