

G5035080

Led Power Supply SLT80-350IL-EU Multi-current up to 350mA 80W

January 07th, 2025, 02:07



DESCRIPTION

Led power supply to incorporate with constant current multi-current output by DIP switch Class I. Quick connection terminals. 200mA 23-54W; 210mA 23.1-56.5W; 220mA 23.1-59W; 230mA 23.1-62W; 240mA 23, 1-64.5W; 250mA 23.1-67.5W; 260mA 23.7-70W; 270mA 23.1-72.5W; 280mA 23.1-75.5W; 290mA 23.1-78W; 300mA 33-80W; 310mA 34, 1-80W; 320mA 35.2-80W; 330mA 36.3-80W; 340mA 37.4-80W; 350mA 38.5-80W.

PRICE

	Lot	P.V.P. excluding VAT
	1	20,18€
	5	18,34€
	10	16,67€
	50	15,60€



Continued on next page >>

G5035080

Led Power Supply SLT80-350IL-EU Multi-current up to 350mA 80W

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS

Weight: 264 Grams

Packging: Box 1 Unit

NOTES

SLR-2021 Compliant. Selectable constant current from 200mA to 350mA by DIP switch.

OTHER FEATURES

Length (mm): 280

Width (mm): 30

High (mm): 22

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 110~270

Intensidad Out (A): 0.2~0.35

Frecuency (Hz): 50~60

Power (W): 23~80

Room Temperature (°C): -20~+50

Critical Temperature (°C): 85

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.9

DOCUMENTS

 [Data Sheet](#)

 [Led Power Supply SLT80-350IL-EU Multi-current up to 350mA 80W](#)

 [MEEI \(Hungary\)](#)