

G5K000P03

Rectangular control board module led to battery GPC

December 22nd, 2024, 04:22



DESCRIPTION

37x25mm rectangular fiberglass plate. With 2 fixing holes with a diameter of 3mm. The plates have a Jumper controller that allows you to choose the luminous flux at 150lm or 250lm. Connectors for 1 or 2 batteries. If only one battery is inserted, the other connector is free. The battery can be connected indistinctly to any of the 2 connectors and must be connected after connecting the touch control. Depending on the selected luminous flux, you can choose to put one or two batteries depending on the necessary autonomy time. Connector for touch control and to micro USB. Independent connectors + and - for the led board. Optional RF connector for remote control.

PRICE

	Lot	P.V.P. excluding VAT
	1	11,84€
	10	10,78€
	50	9,79€
	200	9,32€



G5K000P03

Rectangular control board module led to battery GPC

TECHNICAL SPECIFICATIONS

SYMBOLS



Weight: 11 Grams

CERTIFICADOS



Packging: Box 1 Unit

NOTES

Jumper that allows you to choose 150lm or 250lm. Connectors to 1 or 2 batteries, touch and micro USB. Note: The compatible battery is G5K000P1 and must be connected after touch control.

OTHER FEATURES

Length (mm): 37

Width (mm): 25,1

High (mm): 10,3

Ingress Protection: IP20

Dimmable: SI

DOCUMENTS

 [Data Sheet](#)

 [CE](#)