

ELECTRICAL EQUIPMENT > Korner IP68 Connectors > IP68 Screw connectors
Connectors with screw IP68 cable section 2.5mm² 24A -400V

498M203 - 4531300

Connector with IP68 screws OK-M20 3 poles 2.5mm²

November 21st, 2024, 13:55



DESCRIPTION

3-pole connector. Black PA6.6 polyamide. Self-extinguishing UL.94V0-GWIT775°C. Operating temperature T105°C. Nickel-plated OT58 brass terminals, galvanized steel screws and silicone gasket.

PRICE

Lot	P.V.P. excluding VAT
1	4,36€
25	3,48€
50	3,32€
150	3,16€



Continued on next page >>

ELECTRICAL EQUIPMENT > Korner IP68 Connectors > IP68 Screw connectors
Connectors with screw IP68 cable section 2.5mm² 24A -400V

498M203 - 4531300

Connector with IP68 screws OK-M20 3 poles 2.5mm²

TECHNICAL SPECIFICATIONS

SYMBOLS



Weight: 30 Grams

CERTIFICADOS



Packging: Box 500 Units

NOTES

Cable section 2.5mm²- 24A-400V and AWG14-20A-300V

OTHER FEATURES

Length (mm): 87,7

Width (mm): 24,2

Section (mm²): 2,5

Colour: Black

Voltage In (Vac): 400

Intensidad In (A): 24

Temperature (°C): 105

Ingress Protection: IP68

DOCUMENTS

 [Data Sheet](#)

 [C UR U.S. \(USA-Canada\)](#)

 [Electromagnetic compatibility TÜV SÜD](#)