

ELECTRICAL EQUIPMENT > Korner IP68 Connectors > IP68 Screw derivations  
Derivations with screw IP68 cable section 4mm<sup>2</sup> 32A -400V

498M25Y5 - 4535500

Connector Bypass with screws IP68 OK-M25Y 5 poles 4mm<sup>2</sup>

February 22nd, 2025, 08:36



**DESCRIPTION**

5-pole connector. Black PA6.6 polyamide. Self-extinguishing UL.94V0-GWIT775°C. Operating temperature T105°C. Nickel-plated OT58 brass terminals, galvanized steel screws and silicone gasket

**PRICE**

Lot	P.V.P. excluding VAT
1	8,91€
5	7,12€
15	6,79€
45	6,46€



Continued on next page >>

498M25Y5 - 4535500

Connector Bypass with screws IP68 OK-M25Y 5 poles 4mm<sup>2</sup>

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



### CERTIFICADOS



Weight: 78 Grams

## NOTES

---

Cable section 4mm<sup>2</sup>- 32A-400V and AWG12-30A-300V

## OTHER FEATURES

---

Length (mm): 155

Width (mm): 83

Section (mm<sup>2</sup>): 4

Colour: Black

Voltage In (Vac): 400

Intensidad In (A): 32

Temperature (°C): 105

Ingress Protection: IP68

## DOCUMENTS

---

 [Data Sheet](#)

 [C UR U.S. \(USA-Canada\)](#)

 [Electromagnetic compatibility TÜV SÜD](#)