

ELECTRICAL EQUIPMENT > Korner IP68 Connectors > IP68 Screw derivations  
Derivations with screw IP68 cable section 2.5mm<sup>2</sup> 24A -400V

**498M20X3 - 4533800**

**Connector Bypass with screws IP68 OK-M20X 3 poles 2,5mm<sup>2</sup>**

December 22nd, 2024, 03:09



## DESCRIPTION

3-pole connector. Black PA6.6 polyamide. Self-extinguishing UL.94V0-GWIT775°C. Operating temperature T105°C. Nickel-plated OT58 brass terminals, galvanized steel screws and silicone gasket.

## PRICE

Lot	P.V.P. excluding VAT
1	17,29€
10	13,83€
20	13,17€
60	12,55€



Continued on next page >>

498M20X3 - 4533800

Connector Bypass with screws IP68 OK-M20X 3 poles 2,5mm<sup>2</sup>

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



### CERTIFICADOS



Weight: 91 Grams

## NOTES

---

Cable section 2.5mm<sup>2</sup>- 24A-400V and AWG14-15A-300V

## OTHER FEATURES

---

Length (mm): 109

Width (mm): 104

Section (mm<sup>2</sup>): 2,5

Colour: Black

Voltage In (Vac): 400

Intensidad In (A): 24

Temperature (°C): 105

Ingress Protection: IP68

## DOCUMENTS

---

 [Data Sheet](#)

 [C UR U.S. \(USA-Canada\)](#)

 [Electromagnetic compatibility TÜV SÜD](#)