

B3RE804

Terminal block male-female OK431 FV-SP 4 poles 2.5mm²

January 15th, 2025, 13:43



DESCRIPTION

Plug-in connection strips (male + female) fiberglass 431-FV-SP 4 poles and section 2.5mm². Connection with screws, insulating material polyamide 6-6 25% fiber. Self-extinguishing UL94V0 and temp 150°C. Distance between terminals 8, hole diameter 2.8 . L = 31.1 A = 32.8 H = 14.7

PRICE

	Lot	P.V.P. excluding VAT
	1	2,34€
	10	1,57€
	50	1,31€
	750	1,22€



Continued on next page >>

B3RE804

Terminal block male-female OK431 FV-SP 4 poles 2.5mm²

TECHNICAL SPECIFICATIONS

Weight: 15 Grams

NOTES

Polyamid PA6-6 with 25 % fiber glass auto-extinguible UL94V0 T150 C GWT750 C (EN60695-2-11)

OTHER FEATURES

Length (mm): 31,1

Width (mm): 32,8

High (mm): 14,7

Section (mm²): 2,5

Colour: Tile

Voltage In (Vac): 450

Intensidad In (A): 24

Temperature (°C): 150

Connection: Screw

DOCUMENTS

 [Data Sheet](#)