

 ${\tt LED\ TECHNOLOGY>Flexible\ Led\ Strips\ and\ accessories>Flexible\ Led\ Strips\ IP62-IP63}$ ${\tt Flexible\ Led\ Strips\ IP62-IP63\ 24V}$

LFD224044

Flexible Led strip 5m SMD2835-60led/m. IP62 24V 4,8W/m - 24W 4000K

April 05th, 2025, 02:22



DESCRIPTION

Flexible LED strip at constant voltage D2835 60leds / m 24VDC 24W neutral white 4000K. Supply voltage (Vdc) 24V. Total maximum current (A) 1. Power 4.8W / m; total 24W. Luminosity 408Lm / meter; total 2040Lm. Total length 5 meters. Total number of LEDs 300. Divisible into modules of 6 LEDs every 10cm (one LED every 16.7mm). Degree of protection IP62 for humid environments. Adhesive application on the back. Parallel connection. White PCB color.

PRICE

Lot	P.V.P. excluding VAT
1	31,23€
5	28,43€
10	27,03€

Continued on next page >>



 ${\tt LED\ TECHNOLOGY > Flexible\ Led\ Strips\ and\ accessories > Flexible\ Led\ Strips\ IP62-IP63}}$ ${\tt Flexible\ Led\ Strips\ IP62-IP63\ 24V}$

LFD224044

Flexible Led strip 5m SMD2835-60led/m. IP62 24V 4,8W/m - 24W 4000K

TECHNICAL SPECIFICATIONS

SYMBOLS CERTIFICADOS

















Weight: 159 Grams Packging: Roll 5 Meters

NOTES

Total number LED 300. Divisible every 10cm in modules of 6 (1 LED each 16,6mm). With adhesive.CRI>80

OTHER FEATURES

Length (mm): 5000 Width (mm): 8

High (mm): 3 Colour: White PCB Voltage In (Vdc): 24 Intensidad In (A): 2

Power (W): 4.8 Temperature (°C): -20+50

Room Temperature (°C): -20~+50 Colour Temperature (°K): 4000

Lumen/meter: 408 Angle (º): 120

CRI (≥): 80 Life (Hours): 50000

Ingress Protection: IP62 Dimmable: SI

DOCUMENTS

Data Sheet

L CE

UR (USA)