

G503801B

Alimentation LED CC SLT35-1000IB-UN multi output current 250-1000mA

23 nov. 2024



DESCRIPTION

Built-in Led power supply with constant multi-current output selectable by DIP switch. Output voltage range 2-50V High efficiency.
 Class II. Quick connection terminals.
Selectable outputs: 250mA-12W; 300mA-15W; 350 mA -17W; 400mA-20W; 450mA-22W; 500mA-25W; 550mA-27W; 600mA-30W; 650mA-32W; 700mA, 750mA, 800mA, 850mA, 900mA, 950mA, 1000mA 35W. Protection against open circuit, short circuit, over load and over temperature. Automatic reset. Warranty 5 years.

PRIX

Lot	Prix sans TVA
1	22,18€
5	20,16€
10	18,33€
50	17,13€



G503801B

Alimentation LED CC SLT35-1000IB-UN multi output current 250-1000mA

SPÉCIFICATIONS TECHNIQUES

SYMBOLES



SELV



Pesage: 160 Grammes

Conditionnement: Boîte 1 Unité

REMARQUES

ECO Design ERP. Courant de sortie constant sélectionnable de 250 mA à 1000 mA par commutateur DIP. Modèle sans casquettes bleues. Incorporer

AUTRES CARACTÉRISTIQUES

Longueur (mm): 95,6

Largeur (mm): 39

Hauteur (mm): 30

Couleur: Blanc

Tension In (Vac): 110~277

Tension Out (Vdc): 2~50

Intensidad Out (A): 0.25~1

Fréquence (Hz): 50~60

Puissance (W): 0.5~35

Température Ambiante (°C): -25~+50

Température Critique (°C): 90

Indice de protection: IP20

Dimmable: NO

Facteur de puissance: 0.75-0.9

DOCUMENTS

 [Fiche technique](#)

 [Alimentation LED CC SLT35-1000IB-UN multi output current 250-1000mA](#)

 [C UR US \(USA-Canada\)](#)

 [MEEI \(Hongrie\)](#)

 [Marque de conformité réglementaire Australie](#)