

G503805

Alimentation LED CC SLT45-1050IL-E multi output current 700-1050mA

22 déc. 2024



DESCRIPTION

Led power supply for independent use with constant multi-current output selectable by DIP switch. Output voltage range 27-42V High efficiency. Class II. Quick connection terminals. Selectable outputs: 700mA 18.9-29.4W; 750mA 20.3-31.5W; 800mA 21.6-33.6W; 850mA 22.9-35.7W; 900mA 24.3-37.8W; 950mA 25.6-39.9W; 1000mA 27-42W; 1050mA 28.3-42W. Protection against open circuit, short circuit, overload and overtemperature. Automatic reset. 5 year warranty

PRIX

| Lot | Prix sans TVA |
|-----|---------------|
| 1 | 17,46€ |
| 5 | 15,87€ |
| 10 | 14,44€ |
| 50 | 13,49€ |



G503805


Alimentation LED CC SLT45-1050IL-E multi output current 700-1050mA

SPÉCIFICATIONS TECHNIQUES

SYMBOLES



SELV



Pesage: 148 Grammes

Conditionnement: Boîte 1 Unité

REMARQUES

Conforme à ECO Design ERP. Courant de sortie constant sélectionnable de 700 mA à 1050 mA par commutateur DIP

AUTRES CARACTÉRISTIQUES

Longueur (mm): 139

Largeur (mm): 42

Hauteur (mm): 29,8

Couleur: Blanc

Tension In (Vac): 220~240

Tension Out (Vdc): 27~42

Intensidad Out (A): 0.7~1.05

Fréquence (Hz): 50~60

Puissance (W): 18.9~42

Température Ambiante (°C): -25~+50

Température Critique (°C): 85

Indice de protection: IP20

Dimmable: NO

Facteur de puissance: 0.95

DOCUMENTS

 [Fiche technique](#)

 [Alimentation LED CC SLT45-1050IL-E multi output current 700-1050mA](#)

 [CCC \(Chine\)](#)

 [MEEI \(Hongrie\)](#)

 [Marque de conformité réglementaire Australie](#)