




Saves Your Energy

PRODUCT CARD

10.11.2015

# NAC52S.W

Name:	<b>Coupler</b> White (1, 2, PE, N, 3)
Type:	NAC52S.W
GTIN:	6418677112805
Description:	For flexible, stranded and solid wires. Wire cross-section 0,75-4,0 mm <sup>2</sup> . Strain-relief for cables with outer diameter of 8,6-14,5 mm.
Package:	100/6300
Unit:	PCS



## Technical specification

UL Wire range	12 ... 18 AWG
<b>Ratings</b>	
Rated voltage	250 ... 400 V
Degree of protection	IP20
Rated current	20 A
ETIM class	Plug-in connector for plug-in building installation
<b>Dimensions</b>	
Dimensions l x w x h	60x59x20
Conductor cross-section	0,75 - 4 mm <sup>2</sup>
<b>Temperatures</b>	
Max. operating temperature	+70 °C
Min. installation temperature	+5 °C
Min. operating temperature	-30 °C ( without mechanical stress )
<b>Features</b>	
Pole markings	1,2,PE,N,3
<b>Materials</b>	
Material	Polyamide 66
<b>Colors</b>	
Color	White
<b>US specific</b>	
UL Rated voltage	250 / 400
UL Rated current	16 A

Ensto Finland Oy

Ensio Miettisen katu 2  
P.O.Box 77  
06101 Porvoo, Finland

Tel. +358 204 76 21  
Fax +358 204 76 2750

www.ensto.com