

AcTEC LED DRIVER

Q8H-12V-60W

SPECIFICATION

Description	220-240V LED Driver, Constant voltage Driver
Electrical Characteristics	Ta = 25°C, 220-240Vrms input, standard reference load; unless otherwise specified
Class II, IP20, thermally protected 110, independent driver	

Product Name		Q8H-12V-60W
---------------------	--	-------------

Input Parameters

Rated Input Voltage	Uin	220-240VAC
Input Current (Full load)	Iin	0.45A
Input Frequency	fin	50/60Hz
Maximum Input Power	Pin	69W
Power Factor (Full load)	λ	0.95
THD(Full load)		≤ 15%
Efficiency (Full load)	η	≥ 86%
No-load power		≤ 0.5W
Inrush current		≤ 10.0A
Turn on time		≤ 500ms

Output Parameters

Output Voltage	Vout	12V±5%
Output Current (Full load)	Iout	5.0A
Output Power (Full load)	Pout	60W
Operating Frequency(Full load)	Fout	70KHz
Ripple & Noise		≤ 500mV
Load Regulation		≤ 5%
Line Regulation		≤ 5%

Ambient

Storage Temperature	ts	-20 ... + 70°C
Operating Ambient Temperature	ta	-20 ... + 50°C
Case Temperature at tc Point	tc	90°C
Relative humidity		5 ... 85%

Protection

No Load		Auto-recovery if fault is removed
Over Load		Auto-recovery if fault is removed
Short Circuit		Auto-recovery if fault is removed

System Parameters



Withstand voltage		3.75KVAC, Ileakage<5.0mA,60s
Expected Life		30,000Hours

Compliances and approvals

Safety		EN 61347-2-13
RFI		EN 55015
Harmonics		EN 61000-3-2 Class C
Immunity		EN 61547

Note

1. All parameters NOT specially mentioned are measured at 240VAC input, rated load and 25 of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.
3. Expected Life:tc=80°C,0.2%/1000h failure rate

<p>Physical Parameter</p>  <p>Dimensions(LxWxH): 184x61x32mm Housing Material::PC Plastic Captured Terminal Screw for 0.75~2.5mm²</p>	
--	--