

## SPECIFICATION

Description	220-240V LED Driver, Constant Voltage Driver
Electrical Characteristics	Ta = 25°C, 220-240Vrms input, standard reference load; unless otherwise specified
Class II, IP20, thermally protected 110, independent driver	

<b>Product Name</b>		Q8H-24V-40W
---------------------	--	-------------

### Input Parameters

Rated Input Voltage	Uin	220-240VAC
Input Current (Full load)	Iin	0.25A
Input Frequency	fin	50/60Hz
Maximum Input Power	Pin	47W
Power Factor (Full load)	λ	≥0.95
THD(Full load)		≤15%
Efficiency (Full load)	η	≥88%
No-load power		≤0.5W
Inrush current		≤30.0A
Turn on time		≤500ms

### Output Parameters

Output Voltage	Vout	24V±5%
Output Current (Full load)	Iout	1.7A
Output Power (Full load)	Pout	40W
Operating Frequency(Full load)	Fout	70KHz
Ripple & Noise		≤500mV
Load Regulation		≤5%
Line Regulation		≤5%

### Ambient

Storage Temperature	ts	-20 ...+ 70°C
Operating Ambient Temperature	ta	-20 ...+ 50°C
Case Temperature at tc Point	tc	85°C
Relative humidity		5 ...85%

### Protection

No Load		Auto-recovery if fault is removed
Over Load		Auto-recovery if fault is removed
Short Circuit		Auto-recovery if fault is removed

### System Parameters

Withstand voltage		3.75KVAC, Ileakage<5.0mA, 60S
Expected Life		50,000Hours

### Compliances and approvals

Safety		EN 61347-2-13
RFI		EN 55015
Harmonics		EN 61000-3-2 Class C
Immunity		EN 61547

### Note

1. All parameters NOT specially mentioned are measured at 240VAC input, rated load and 25 of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.
3. Expected Life:tc=80°C,0.2%/1000h failure rate

### Physical Parameter

Dimensions(LxWxH): 166x52x24mm

Housing Material::PC Plastic

Captured Terminal Screw for 0.75~2.5mm<sup>2</sup>