

Certificate of Conformity

Global-Mark Pty. Ltd., certify the electrical equipment described hereunder complies with standards listed herein and notifies the certificate holder to affix the Regulatory Compliance Mark (RCM) mark to products of the same type provided that the requirements of all relevant parts of AS/NZS 4417 applicable to the article are fulfilled. In placing the RCM mark on the product, the Responsible Supplier makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein. – **This Certificate meets the requirements of a Recognised External Certification Scheme (RECS) including the rules of the EESS.**

CERTIFICATION AND CERTIFICATE HOLDER DETAILS

Company Name	TCI Telecomunicazioni Italia S.R.L.			
Address	Saronno (VA) Via Parma 14 Cap - - 21047 Italy			
Client ID	105895	Global-Mark File Number:	105895-012	System 1 Approval
Certificate Number	GMA-506924-EA	Revision Number	01	
Certification Standard(s)	AS 61347.2.13:2018 Lamp Control Gear - Part 2-13: Particular Requirements For D.C Or A.C Supplied Electronic Control Gear For Led Modules.			
Type of Certification	Electrical Safety Product	Scheme	Global-Mark Electrical Product Safety Certification Scheme	

CERTIFICATE DATES

Certificate Issue Date	28/02/2020
Certificate Last Update Date	1/03/2020
Certification Expiry Date	28/02/2025

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

CERTIFIED ELECTRICAL EQUIPMENT				
Declared Article	Product Description	Trade Name	Model Number	Rating
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US ZB3	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US ZB3	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US CASAMBI	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US CASAMBI	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US BLL	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US BLL	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US BLL EX	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US BLL EX	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	MP 50 K3	Vin=100-240 V, 50/60 Hz,max. 0,55 A, Po=25-50 W, Io=0,35-1,05 A, Uout=90 V, Vo=48 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US cod. 127411	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV WR	Vin=100-240 V, 50/60 Hz,max. 0,52 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US cod. 151411	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI WR	Vin=100-240 V, 50/60 Hz,max. 0,52 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US MIDNIGHT	Vin=100-240 V, 50/60 Hz,max. 0,55 A, Po=25-50 W, Io=0,35-1,05 A, Uout=90 V, Vo=48 V

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager

Certificate of Conformity

Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV ZB3	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US BILEVEL	Vin=100-240 V, 50/60 Hz,max. 0,55 A, Po=25-50 W, Io=0,35-1,05 A, Uout=90 V, Vo=48 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV CASAMBI	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US BILEVEL N	Vin=100-240 V, 50/60 Hz,max. 0,55 A, Po=25-50 W, Io=0,35-1,05 A, Uout=90 V, Vo=48 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV BLL	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US PLV	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV BLL EX	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US DALI cod. 127413	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV cod. 125502	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY US DALI cod. 151413	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=25-60 W, Io=0,35-1,05 A, Uout=90 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV cod. 151502	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	MP 50 K3	Vin=100-240 V, 50/60 Hz,max. 0,55 A, Po=25-50 W, Io=0,35-1,05 A, Uout=90 V, Vo=48 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV 1-10V S	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV WR	Vin=100-240 V, 50/60 Hz,max. 0,52 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV PLV	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI WR	Vin=100-240 V, 50/60 Hz,max. 0,52 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI cod. 125504	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV ZB3	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI cod. 151504	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV CASAMBI	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI 40 cod. 125506	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-40 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV BLL	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI 40 cod. 151506	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-40 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV BLL EX	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	MP 5V SV K3	Vin=110-240 V, 50/60 Hz,max. 0,55 A, Po=20-50 W, Io=0,35-1,05 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV cod. 125502	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV cod. 127414	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV cod. 151502	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV cod. 151414	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV 1-10V S	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV DALI cod. 127409	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV PLV	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV DALI cod. 151409	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI cod. 125504	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV MIDNIGHT	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI cod. 151504	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-50 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV BILEVEL	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI 40 cod. 125506	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-40 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV BILEVEL N	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI 40 cod. 151506	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=18,5-40 W, Io=0,35-1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY STREET HV	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	MP 50 SV K3	Vin=110-240 V, 50/60 Hz,max. 0,55 A, Po=20-50 W, Io=0,35-1,05 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI IPR1	Vin=110-240 V, 50/60 Hz,max. 0,46 A, Po=3,5-70 W, Io=0,35-1,4 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV cod. 127414	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI IPR1 LO	Vin=110-240 V, 50/60 Hz,max. 0,46 A, Po=3,5-70 W, Io=0,35-1,4 A, Uout=60 V

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV cod. 151414	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 70/1400 SV	Vin=110-240 V, 50/60 Hz,max. 0,46 A, Po=70 W, Io=1,4 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV DALI cod. 127409	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 70/1400 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,46 A, Po=70 W, Io=1,4 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV DALI cod. 151409	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 60/1200 SV	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-60 W, Io=1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV MIDNIGHT	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 60/1200 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-60 W, Io=1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV BILEVEL	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 52/1050 SV	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-52 W, Io=1,05 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY HV BILEVEL N	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 52/1050 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-52 W, Io=1,05 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY STREET HV	Vin=110-240 V, 50/60 Hz,max. 0,44 A, Po=28-60 W, Io=0,25-0,7 A, Uout=119 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 45/900 SV	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-45 W, Io=0,9 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI IPR1	Vin=110-240 V, 50/60 Hz,max. 0,46 A, Po=3,5-70 W, Io=0,35-1,4 A, Uout=60 V

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 45/900 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-45 W, Io=0,9 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	DC MAXI JOLLY SV DALI IPR1 LO	Vin=110-240 V, 50/60 Hz,max. 0,46 A, Po=3,5-70 W, Io=0,35-1,4 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 35/700 SV	Vin=110-240 V, 50/60 Hz,max. 0,37 A, Po=35 W, Io=0,7 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 70/1400 SV	Vin=110-240 V, 50/60 Hz,max. 0,46 A, Po=70 W, Io=1,4 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 35/700 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,37 A, Po=35 W, Io=0,7 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 70/1400 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,46 A, Po=70 W, Io=1,4 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 25/500 SV	Vin=110-240 V, 50/60 Hz,max. 0,26 A, Po=25 W, Io=0,5 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 60/1200 SV	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-60 W, Io=1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 25/500 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,26 A, Po=25 W, Io=0,5 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 60/1200 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-60 W, Io=1,2 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 52/1050 SV	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-52 W, Io=1,05 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 52/1050 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-52 W, Io=1,05 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 45/900 SV	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-45 W, Io=0,9 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 45/900 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,42 A, Po=40-45 W, Io=0,9 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 35/700 SV	Vin=110-240 V, 50/60 Hz,max. 0,37 A, Po=35 W, Io=0,7 A, Uout=60 V

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager




Certificate of Conformity

Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 35/700 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,37 A, Po=35 W, Io=0,7 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 25/500 SV	Vin=110-240 V, 50/60 Hz,max. 0,26 A, Po=25 W, Io=0,5 A, Uout=60 V
Power Supply or Charger	Power Supply for LED module	TCI TELECOMUNICAZIONI ITALIA S.R.L.	IPR1 25/500 SV LO	Vin=110-240 V, 50/60 Hz,max. 0,26 A, Po=25 W, Io=0,5 A, Uout=60 V

RELEVANT TRADEMARK (S)

COMMENTS OR CONDITIONS ON THE CERTIFICATION
Classified as NON IC not suitable for residential installations 2020/03/01 Modification 1 - add model DC MAXI JOLLY SV 1-10V S

End of document

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager

